



Solution to minimize leading edge erosion on turbine blades

Bech, Jakob Ilsted; Bak, Christian; Vejen, Flemming; Madsen, Martin Bonde; Bayar, Mertcan; Skrzypinski, Witold Robert; Kusano, Yukihiro; Halling, Kaj M. ; Saldern, Morten ; Tilg, Anna-Maria

Total number of authors:

12

Publication date:

2019

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Bech, J. I., Bak, C., Vejen, F., Madsen, M. B., Bayar, M., Skrzypinski, W. R., Kusano, Y., Halling, K. M., Saldern, M., Tilg, A.-M., Fæster, S., & Johansen, N. F.-J. (2019). *Solution to minimize leading edge erosion on turbine blades*. Poster session presented at WindEurope Conference and Exhibition 2019, Bilbao, Spain.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Solution to minimize leading edge erosion on turbine blades

Jakob Ilsted Bech; Christian Bak; Flemming Vejen; Martin Bonde Madsen; Mertcan Bayar; Witold Robert Skrzypinski; Yukihiro Kusano; Kaj Halling; Morten Saldern; Anna-Maria Tilg; Søren Fæster; Nicolai Frost-Jensen Johansen
DTU, DMI, R&D, E.On, Vestas and Vattenfall

Abstract

A novel method is proposed to maximize the value of operating fleet of wind turbines suffering leading edge erosion. This method will ensure longer lifetime and reduce repair cost.

The challenge is to balance the cost of repair, downtime of wind turbines and loss of energy production due to leading edge erosion. Current practice is to inspect the turbines and repair when it is considered necessary from the point of loss of Annual Energy Production (AEP) or structural failure. The cost for repair is high and tends to get higher while the weather windows get narrower as turbines increase in size and stand further away from service ports.

The novel method called 'erosion safe mode' can be implemented readily to the operating fleet of turbines as well as to new wind farms. The method is cost effective.

Research hypothesis



Methods

Rain erosion at leading edges is much dependent upon the occurrence of rain and wind. The rate of leading edge erosion is higher during heavier rain and stronger winds. High non-linearity exists between different rain-wind climate conditions; thus to predict optimal erosion safe mode reliable information on the rain and wind conditions is needed.

The erosion safe mode method is simple as follows. The tip speed is reduced say 30% during the most extreme rain-wind events, 20% during lesser extreme events and 10% during moderate events, see Bech *et al.* 2018.

Examples of erosion safe mode at Danish land of offshore sites are calculated based on 16 years of 10 minute observations of rain intensity (mm/h) and wind speed at meteorological stations. The joint distributions of the exceedance levels of rain intensity as a function of wind speeds are used as input in a model for the leading edge erosion. The SN-curves are based on novel results from rain erosion testing in a whirling arm laboratory with variable speeds and drop sizes. The specimens are similar to current days wind turbine blades.

Implementation

In order to implement the erosion safe mode only two things have to be in place:

- Rain sensor at or near wind turbine, plus now-casting of rain from weather service.
- Turbine control established to reduce tip speed based on rain-wind input and desired lifetime.

First, it is proposed to use maintenance-free rain sensor giving information on drop-let size distribution and rain rate. The now-casting typically will be based on tailor-made weather service with the expected rain minutes to hours ahead. The erosion safe mode control should only be activated in case both provide valid rain data (or alternative, two rain sensors located at turbine site to ensure redundancy).

Second, the choice of erosion safe mode control will be based on the desire from the wind turbine operator to enable longer leading edge lifetime according to the internal business model, the turbine type, leading edge protection available and the prevailing rain-wind climate.

Case of savings

As example for real-life savings a case is presented in brief below. Imagine a turbine with maximum tip speed of 90 m/s operating in a rain-wind climate in which violent rain (>20 mm/h) occurs 0.02% of time (1.8 hours during one year), heavy rain (>10 mm/h) occurs 0.1% of time (8.8 hours) and moderate rain (>5 mm/h) occurs 1% of time (88 hours). For normal operation, i.e. 90 m/s during all conditions the selected wear model (SN-curve) estimates that the blade can only operate 3.5 hours before failure due to violent rain, 79 hours before failure due to heavy rain and 3600 hour before failure due to moderate rain. In other words, the fraction of lifetime spent in violent rain corresponds to 51% of the total erosion, while heavy rain causes 11% of erosion and moderate rain causes 2.4% of wear. The sum of wear gives expected lifetime of the blade 1.6 years. Reducing the tip speed to 70 m/s in violent rain and 80 m/s in heavy rain gives expected lifetime of 10.4 year because wear rates are much reduced.

The cost calculation for the above example is as follows. In case power cost is at 50 euro/MWh, repair cost at 10.000 euro per rotor and inspection cost at 500 euro per rotor, the loss in income is **9.2% with normal strategy and 3.3% for erosion safe mode** (both percentages are compared to reference of maintenance free blade). Further assumptions are Weibull A of 7 m/s and AEP loss due to aerodynamic degradation of 0.964 and 0.974, respectively, for the normal and erosion safe mode operations

Conclusions

The novel method called 'erosion safe mode' may be implemented readily to the operating fleet of turbines.

The method appears to be cost effective from the calculations.

Full scale testing is in planning.

References and Acknowledgement

- Bech, J.I., Hasager, C.B., Bak, C. 2018 Extending the life of wind turbine blade leading edges by reducing the tip speed during extreme precipitation events. *Wind Energy Science*, 3, 729-748, 2018, <https://doi.org/10.5194/wes-3-729-2018> <https://doi.org/10.5194/wes-2017-62>
- We gratefully acknowledge funding from Innovation Fond Denmark for the EROSION project, Project ID 6154-00018B.

MEET US AT 1-F41

