



Leading edge erosion of wind turbine blades: Need for raindrop-size measurements

Tilg, Anna-Maria; Hasager, Charlotte Bay; Vejen, Flemming; Nielsen, Morten; Bech, Jakob Ilsted

Publication date:
2019

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Tilg, A.-M., Hasager, C. B., Vejen, F., Nielsen, M., & Bech, J. I. (2019). *Leading edge erosion of wind turbine blades: Need for raindrop-size measurements*. Abstract from 6th International Conference Energy & Meteorology, Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

6th International Conference Energy & Meteorology: Abstract Submission

Days	Leading edge erosion of wind turbine blades: Need for raindrop-size measurements (754)	^
Tuesday, 25th J...	Anna-Maria Tilg ¹ , Charlotte Hasager ¹ , Flemming Vejen ² , Morten Nielsen ¹ , Jakob Bech ¹	∨
Wednesday, 26t...	1. Department of Wind Energy, Technical University of Denmark, Roskilde, Denmark	⋈
Thursday, 27th ...	2. Danish Meteorological Institute, Copenhagen, Denmark	
Search	Leading edge erosion (LEE) of wind turbine blades is the degradation of material at the leading edge of the turbine blades. It causes a loss of the annual energy production and can lead to structure failure of the blade material. In northern Europe LEE appears to be faster and more frequent at wind farms located offshore than at onshore wind farms. First results show that rainfall events at high tip speeds seem to have a high influence on the LEE beside precipitation events with hail (Bech et al. 2018). To improve our understanding of the influence of rain on the LEE process, it is important to analyze the spatio-temporal variation of raindrop-size distributions (DSD).	
Speakers (/spea...	Five years DSD measurements from a disdrometer at an up-country side in Denmark provided by the Danish Meteorological Institute (DMI) show in general a higher number of raindrops in summer and autumn than in winter and spring. Raindrops with a diameter larger than 1 mm are more frequent in the same time of the year. However, the concentration of drops with different diameters varies like the total amount of precipitation from year to year.	
	Although wind measurements are available over ocean, no longer time series of DSD over ocean exist. Therefore, disdrometers to measure the raindrop size have been installed recently at the west coast of Denmark in cooperation with DMI to get an impression of the conditions offshore. These measurements will be compared with the DSD data from the up-country side. With this comparison, we try to understand more about the more pronounced LEE process at offshore wind farms.	
	Overall, an option for reducing LEE of wind turbine blades could be forecasting severe precipitation events. Therefore, precipitation measurements and forecasts, especially offshore, will become important for wind industry.	