



Two phase flow modelling on realistic discrete fracture models

Andrianov, Nikolai; Nick, Hamid

Publication date:
2019

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Andrianov, N., & Nick, H. (2019). *Two phase flow modelling on realistic discrete fracture models*. Abstract from Danish Hydrocarbon Research and Technology Centre Technology Conference 2019, Kolding, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Danish Hydrocarbon Research and Technology Centre Technology Conference 2019

Two phase flow modelling on realistic discrete fracture models

Name of authors and affiliations: Nikolai Andrianov and Hamid M. Nick

Presenting author: Nikolai Andrianov

Is the presenting author a research assistant/MSc/PhD student/Postdoc? Yes

We analyze the waterflood performance using an outcrop-based model, representative of North Sea fractured chalk reservoirs. To this end, we consider published data on the fracture geometry of Lägerdorf quarry in northern Germany and create a two-dimensional Discrete Fracture-Matrix (DFM) outcrop-based model, populated with the rock and fluid properties, typical for North Sea oil reservoirs. We conduct several DFM simulations to study the dependency of oil recovery factor with respect to water injection rate under uncertainty in fracture apertures and orientations, using both sea and low salinity water as injection fluids. Based on simulation results, we show that if there is a noticeable impact of fractures on the flow, the slower injection rates lead to higher recovery in terms of water pore volumes injected. The main factor influencing the recovery efficiency is whether there is a direct communication between the inflow and outflow boundaries via highly conductive fractures. However, if the fractures' apertures in the direct communication path are small enough, the capillary forces can counterbalance the viscous displacement in fractures thus leading to better recovery. We demonstrate that commonly used statistical measures of fractures orientation and connectivity cannot predict this type of behavior

