



A numerical study of the influence of pilot fuel injection timing on air-fuel mixing and combustion of a dual fuel, two-stroke marine engine

Nemati, Arash; Ong, Jiun Cai; Pang, Kar Mun; Walther, Jens H.

Publication date:
2020

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Nemati, A., Ong, J. C., Pang, K. M., & Walther, J. H. (2020). *A numerical study of the influence of pilot fuel injection timing on air-fuel mixing and combustion of a dual fuel, two-stroke marine engine*. Abstract from 73rd Annual Meeting of the American Physical Society, Division of Fluid Dynamics (APS DFD 2020), Chicago, Illinois, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Abstract Submitted
for the DFD20 Meeting of
The American Physical Society

A numerical study of the influence of pilot fuel injection timing on air-fuel mixing and combustion of a dual fuel, two-stroke marine engine¹

ARASH NEMATI, JIUN CAI ONG, Technical University of Denmark, KAR MUN PANG, JENS H. WALTHER, MAN Energy Solutions — Three-dimensional computational fluid dynamic (CFD) simulations of a dual fuel marine engine are conducted where a small amount of pilot diesel fuel is injected near top dead center, follow by a direct injection of natural gas. A skeletal chemical n-heptane mechanism (56 species) which consists of the methane oxidation reaction pathways, is utilized to simulate the oxidation of diesel and methane as well as the formation of emissions in the dual-fuel combustion. The n-heptane and methane IDT were evaluated by performing homogeneous reactor calculations. A phenomenological soot model is also considered to investigate the formation of soot. The CFD model is evaluated using the experimental pressure measurement. Effects of pilot diesel fuel injection timing is studied with an emphasis on the associated combustion and emission characteristics. It is found that by retarding the pilot fuel injection timing, a larger unburned methane cloud is formed inside the combustion chamber prior to being ignited by the pilot fuel which leads to high heat release rate. Furthermore, retarding the pilot fuel injection timing leads to a higher amount of formed soot as well as higher unburned CH₄ and CO emissions. On the other hand, advancing the diesel injection timing increases the NO emission.

¹The authors gratefully acknowledge the financial support from the Independent Research Fund Denmark (DRF) and MAN Energy Solutions under the grant number 8022-00143B.

Arash Nemati
Technical University of Denmark

Date submitted: 03 Aug 2020

Electronic form version 1.4