



Seasonal heat storage in underground warm water stores Construction and Testing of a 500 m³ store

Hansen, Kurt K.; Hansen, Preben N.

Publication date:
1983

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Hansen, K. K., & Hansen, P. N. (1983). *Seasonal heat storage in underground warm water stores: Construction and Testing of a 500 m³ store*. Technical University of Denmark, Department of Civil Engineering.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

SEASONAL HEAT STORAGE IN UNDERGROUND WARM WATER STORES
(CONSTRUCTION AND TESTING OF A 500 M³ STORE)

Authors : Kurt K. Hansen, Preben N. Hansen
Contract number : ESA-S-162-DK (G)
Duration : 20 months 1 November 1981-30 June 1983
Total budget : Dkr. 1.000.000 CEC contribution : 50%
Head of project : Preben N. Hansen
Contractor : Thermal Insulation Laboratory
Address : Technical University of Denmark
Building 118
DK - 2800 Lyngby
Denmark

Summary

The project contains the projection, the construction and the testing of the efficiency of a 500 m³ warm water store. The aims of the project are:

- gathering practical experience with the actual realization of the pilot plant;
- monitoring the overall behaviour of the storage system;
- verification and modification of the digital computer program.

In this paper the results of the first phase, the examination of the soil conditions on the site of the store and the projection of the storage system, are given.

1. Introduction

On the basis of the preliminary studies done by Preben N. Hansen et al. [1], [2], [3], [4] concerning the heat losses from the store and on the basis of a work [5] done by the Danish firm Dipco Engineering, Virum, concerning possible principles of construction, projection of a 500 m³ store is carried out. The site of the store is on our University campus, see figure 1.

The project contains the following phases:

- a. Detailed examination of the soil conditions on the site of the store.
- b. Using the results from a) detailed projection is performed.
- c. Execution of the construction. The construction is financed by the Danish Ministry of Energy.
- d. Experimentation. Tests are made to determine the storage efficiency.
- e. Verification and modification of the digital computer program.
- f. Reporting.

The results of phase a. and b. will be given in this paper.

2. Examination of the soil conditions

The soil conditions are determined by the Danish Geotechnical Institute. Two continuous borings are made to collect samples for identification of the soil types in order to determine the porosity of the soil in the field. In the laboratory the water content, the dry density, the shear strength, the grainsize distribution, the degree of saturation and the thermal properties are determined.

In one of the boreholes a standpipe is installed to check the case of a secondary groundwater pressure (the primary groundwater is situated more than 40 m below the surface of the ground). In the other borehole a tube with five temperature sensors is placed. A photograph of the boring is shown in figure 2.

2.1 Determination of the thermal properties

To determine the thermal conductivity of moist soil a diagram is given in the literature [6]. The diagram is shown in figure 3 and the entry values are the quartz-content, the dry density and the degree of saturation. Depending on "course-grained" or "fine-grained" soil in the example in the diagram the conductivity is found to be 1.15 W/m⁰C or 0.90 W/m⁰C.

It should be mentioned that some of the conductivities found by the diagram are checked in the laboratory using the instrument shown in figure 4.

To determine the heat capacity of moist soil a diagram is given in the literature [7]. The diagram is shown in figure 5 and the entry values are the porosity and the degree of saturation. From the knowledge of the thermal conductivity and the heat capacity, the thermal diffusivity α is found by the relation $\alpha = \lambda/C$.

The results are given in figure 6. The soil can be de-

scribed roughly as a 4-5 m thick layer of clay. Below this layer of clay is water saturated sand (different degrees of saturation). The thermal conductivity lies between $0.8 \text{ W/m}^\circ\text{C}$ and $2.2 \text{ W/m}^\circ\text{C}$, and the thermal diffusivity lies between $17.0 \text{ m}^2/\text{year}$ and $31.4 \text{ m}^2/\text{year}$.

3. Projection of the storage

The store is digged into the ground ending up with a pyramidal geometry (see figure 7). The ground surface is made waterproof by use of a plastic liner. (No insulation materials are used on this surface). The top is heat insulated and protected against evaporation and against the weather by use of a plastic liner.


The heat input is generated by an oil burner simulating one or more different types of solar collectors.

4. Conclusion

A detailed examination of the soil conditions and a detailed projection of the storage have been made. The construction of the storage has started this month.

5. Literature references

- [1] Hansen, P.N., Analytical description of the heat losses from underground thermal seasonal heat stores. Paper presented at the U.S. Department of Energy Conference "Seasonal Thermal Energy Storage", October 19-21, 1981, Seattle, Washington, U.S.A.
- [2] Hansen, P.N., Seasonal Heat Storage in Hot Water Stores. Paper presented at the International Conference on Numerical Methods in Thermal Problems, July 2-6 1979, Swansea.
- [3] Hansen, P.N., Varmetab fra store varmelagre, (Heat losses in big heat stores). 1979. Thermal Insulation Laboratory, Technical University of Denmark.
- [4] Lawaetz, H. and Hansen, P.N., Solvarmesystem med sæsonlagring - et projektforslag, (A Solar Energy System using Seasonal Heat Storage - a Proposal). Report No. 78-39, 1978. Thermal Insulation Laboratory, Technical University of Denmark.
- [5] Dipco Engineering, Preliminary study of the construction principles to be used building seasonal hot water stores in the ground (in Danish). December 1979. Thermal Insulation Laboratory, Technical University of Denmark.
- [6] The Royal Norwegian Council for Scientific and Industrial Research and the Public Roads Administration's Committee on FROST ACTION IN SOILS, No. 1-17. Oslo 1970-1976.
- [7] Balstrup, T., Varmepumpeanlæg - Varmeovergangsforhold i jord, (Heat pumps - heat flows in soil). Technological Institute, Copenhagen, 1977.



NOTE : λ is thermal conductivity
 α thermal diffusivity

Figure 6. Schematic soil strata and the thermal properties.




Figure 7. The 500 m³ heat storage