



Biodegradation testing of chemicals with high Henry's constants – separating mass and effective concentration reveals higher rate constants

Birch, Heidi; Andersen, Henrik Rasmus; Comber, Mike; Mayer, Philipp

Published in:
SETAC Europe 27th Annual Meeting Abstract Book

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Birch, H., Andersen, H. R., Comber, M., & Mayer, P. (2017). Biodegradation testing of chemicals with high Henry's constants – separating mass and effective concentration reveals higher rate constants. In *SETAC Europe 27th Annual Meeting Abstract Book*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Biodegradation testing of chemicals with high Henry's constants – separating mass and effective concentration reveals higher rate constants

Heidi Birch, Henrik R. Andersen, Mike Comber, Philipp Mayer

Technical University of Denmark, Department of Environmental Engineering, Bygningstorvet, Building 115, 2800 Kgs. Lyngby, Denmark. hbir@env.dtu.dk, hran@env.dtu.dk, philm@env.dtu.dk

Mike Comber Consulting, Bridford, Exeter, UK. mike.comber42@btinternet.com

During simulation-type biodegradation tests, volatile chemicals will continuously partition between water phase and headspace. This study addressed how (1) this partitioning affects biodegradation test results and (2) it can be accounted for by combining mass balance and dynamic biodegradation models. An aqueous mixture of 9 (semi)volatile chemicals was first prepared using passive dosing and then diluted with environmental surface water to produce test systems containing concentrations in the ng/L to µg/L range. After incubation for 2 hours to 4 weeks, automated Headspace Solid Phase Microextraction (HS-SPME) was applied directly on the test systems to measure substrate depletion by biodegradation relative to abiotic controls. HS-SPME was also applied to determine air to water partitioning ratios. Water phase biodegradation rate constants, k_{water} , were up to 72 times higher than test system biodegradation rate constants, k_{system} . True water phase degradation rate constants facilitate extrapolation to other air-water systems and are more suitable input parameters for aquatic exposure and fate models. As such, they should be considered more appropriate for risk assessments than test system rate constants.

Keywords: Biodegradation, Surface water, partitioning, degradation