



MoS₂ nanostructures with tailored dimensionality

Ghimire, Ganesh; Ulaganathan, Rajesh; Miakota, Denys Igorevich; Ilchenko, Oleksii; Canulescu, Stela

Publication date:
2023

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Ghimire, G., Ulaganathan, R., Miakota, D. I., Ilchenko, O., & Canulescu, S. (Accepted/In press). *MoS₂ nanostructures with tailored dimensionality*. Abstract from 2023 MRS Spring Meeting & Exhibit, San Francisco, California, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

MoS₂ nanostructures with tailored dimensionality

Ganesh Ghimire¹, Rajesh Ulaganathan¹, Denys I. Miakota¹, Oleksii Ilchenko², and Stela Canulescu*¹

¹Department of Photonics Engineering, Technical University of Denmark, DK-4000 Roskilde, Denmark

²Department of Health Technology Nanoprobes, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

The ability to manipulate the electrical, optical and magnetic properties of two-dimensional (2D) transition metal dichalcogenides (TMDs) via substitutional doping, defects, electrostatic doping, and charge transfer has led to many exciting opportunities for their utilization¹⁻³. This includes fundamental studies and integration in optoelectronic devices, such as solar cells, photodetectors, laser diodes, and light-emitting diodes^{4,5}. Similarly, one-dimensional (1D) structures of TMDs, such as WS₂ nanorods, have been shown to exhibit striking functionalities compared to their 2D counterparts, such as enhanced photovoltaic effect in bulk and the absence of a p-n junction^{5,6}.

Currently, there are no synthetic methods to control the shape of TMDs from 1D to 2D and, finally, 3D. This paper will discuss a novel approach to synthesising TMD structures with tunable shapes via the growth of transition metal oxide, such as MoOx, by Pulsed Laser Deposition (PLD) followed by conversion to 1D, 2D, or multi-crystal MoS₂. This synthesis procedure is a similar approach described in our previous work^{7,8}, except that alkali was added during the conversion. The morphological studies based on scanning electron microscopy (SEM) and atomic force microscopy (AFM) images reveal an anisotropic growth quasi-1D and highly stacked MoS₂ crystals with preferred (AA(A-...)) stacking orientation on (0001) sapphire. AFM images of the MoS₂ nanoribbons disclose the formation of monolayers at the edges of the nanoribbons, particularly at a high sulfurisation temperature (800°C). At moderate temperatures (~600°C), the extension of the 2D structures outward of the nanoribbons is less pronounced, indicating that nanoribbons probably emerge from 1D ribbons. The conversion/formation mechanism of 1D/3D MoS₂ will be discussed via temperature-dependence studies under an S-rich environment.

The 1D- MoS₂ and (AA(A-...)) stacked- MoS₂ crystals exhibit a high second harmonic generation (SHG) signal, which is an indication of a preferential non-centrosymmetric stacking orientation in MoS₂. Similarly, the Raman spectra in 1D and 3D-stacked crystals have distinct peak positions and ratios of the out-of-plane (A_{1g}) and in-plane (E_{2g}¹) phonon frequency modes. Similarly, the Raman spectra of the 1D and 2D- MoS₂ show distinct signatures as a function of the polarisation of the light. Finally, we will discuss that the 1D- MoS₂ devices offer a strong photocurrent response under light, which is highly tunable as a function of the laser power and polarization.

The experimental results reveal the growth of single-crystalline quasi-1D MoS₂ nanoribbons and their potential use in future optoelectronic applications.

References

1. Hong, X. *et al.* Ultrafast charge transfer in atomically thin MoS₂/WS₂ heterostructures. *Nat Nano* **9**, 682–686 (2014).
2. Tang, J. *et al.* In Situ Oxygen Doping of Monolayer MoS₂ for Novel Electronics. *Small* **16**, 2004276 (2020).
3. Li, M. *et al.* P-type Doping in Large-Area Monolayer MoS₂ by Chemical Vapor Deposition. *ACS Applied Materials & Interfaces* **12**, 6276–6282 (2020).
4. Tsai, M.-L. *et al.* Monolayer MoS₂/Si heterojunction Solar Cell. *ACS Nano* **8**, 8317–8322 (2014).
5. Lopez-Sanchez, O., Lembke, D., Kayci, M., Radenovic, A. & Kis, A. Ultrasensitive photodetectors based on monolayer MoS₂. *Nature Nanotechnology* **8**, 497–501 (2013).
6. Zhang, Y. J. *et al.* Enhanced intrinsic photovoltaic effect in tungsten disulfide nanotubes. *Nature* **570**, 349–353 (2019).
7. Bertoldo, F. *et al.* Intrinsic defects in MoS₂ grown by pulsed laser deposition: From monolayers to bilayers. *ACS Nano* **15**, 2858–2868 (2021).
8. Miakota, D. *et al.* A Facile Strategy for the Growth of High-Quality Tungsten Disulfide Crystals Mediated by Oxygen-Deficient Oxide Precursors. *Nanoscale* (2022).