



Fully Sulfonated Graft Copolymer Blends - a Structure-Property Relationship Study

Nielsen, Mads Møller; Yang, Ami C.C.; Jankova Atanasova, Katja ; Hvilsted, Søren; Holdcroft, Steven

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Nielsen, M. M., Yang, A. C. C., Jankova Atanasova, K., Hvilsted, S., & Holdcroft, S. (2012). *Fully Sulfonated Graft Copolymer Blends - a Structure-Property Relationship Study*. Abstract from 3rd CARISMA International Conference on Medium and High Temperature Proton Exchange Membrane Fuel Cells, Copenhagen, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Fully Sulfonated Graft Copolymer Blends – a Structure-Property Relationship Study

Mads M. Nielsen¹, Ami C. C. Yang², Katja Jankova¹, Søren Hvilsted¹ and Steven Holdcroft²

¹Department of Chemical and Biochemical Engineering, Danish Polymer Centre, Technical University of Denmark, DTU, DK-2800 Kgs. Lyngby, Denmark

²Department of Chemistry, Simon Fraser University, Burnaby, BC, V5A 1S6, Canada
mon@kt.dtu.dk

PerFluoroSulfonic Acids (PFSA) currently predominate as commercial state-of-the-art low temperature Proton Exchange Membranes (PEM), yet they suffer from especially high cost. Hence research to find alternatives is ongoing as large-scale commercialization of hydrogen powered PEM fuel cell cars in 2015 is approaching [1]. The current study is a continuation of the previously presented work by Holdcroft et al. [2 – 3]. Post-sulfonated (s) poly(vinylidene fluoride-co-chlorotrifluoroethylene)-g-polystyrene (P(VDF-co-CTFE)-g-sPS) at three different graft lengths are blended with PVDF to contain sPS volume fractions similar to that of a reference P(VDF-co-CTFE)-g-sPS with a different graft density and graft length. Proton conductivities are measured at 55-95% Relative Humidity (RH) and 25-80 °C, and water uptake is followed by dynamic vapor sorption. P(VDF-co-CTFE)-g-sPS show stronger dependence on both RH and temperature than benchmark PFSA Nafion[®], with superior conductivities by up to a factor of two at 95% RH.




Figure 1. Proton conductivity is measured at various relative humidities and temperatures.

References

- [1] Various authors, The Fuel Cell Today Industry Review 2011, www.fuelcelltoday.com, 16.04.12
- [2] Tsang, E. M. W.; Zhang, Z.; Shi, Z.; Soboleva, T.; Holdcroft, S. *J. Am. Chem. Soc.* **2007**, 129, 15106-15107
- [3] Tsang, E. M. W.; Zhang, Z.; Yang, A. C. C.; Shi, Z.; Peckham, T. J.; Narimani, R.; Frisken, B. J.; Holdcroft, S. *Macromolecules* **2009**, 42, 9467-9480.