



Optimizing the microstructure of dissipative materials

Andreassen, Erik; Lazarov, Boyan Stefanov; Jensen, Jakob Søndergaard

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Andreassen, E., Lazarov, B. S., & Jensen, J. S. (2012). *Optimizing the microstructure of dissipative materials*. Paper presented at International Workshop on Computational Mechanics of Materials, Baltimore, MD, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Optimizing the microstructure of dissipative materials

Erik Andreassen[†], Boyan S. Lazarov, Jakob Søndergaard Jensen

Department of Mechanical Engineering, Technical University of Denmark, Nils Koppels Allé, Building 404, Denmark

[†]erand@mek.dtu.dk

ABSTRACT

The aim of this work is to present a method to design material microstructures with high dissipation using topology optimization. In order to compute the macroscopic energy dissipation in periodic structures, we focus both on capturing the physical dissipation mechanism and to find the effective macroscopic dissipation.

The effective elastic material properties of a periodic structure can be found numerically using homogenization as describe in e.g. (Guedes and Kikuchi, 1990). For dissipative materials a quasi-static approach can be used to find the homogenized complex elasticity tensor, and thereby the material's loss factor, however, only for large wave lengths (small wave numbers) and constant material parameters (Andreasen et al., 2012). An alternative way to determine the material's loss factor is to consider the material's band diagram (Sigalas and Economou, 1992), from which the loss factor can be deduced.

Designs obtained by e.g. maximizing the material's loss factor for a given frequency range will be presented. The method will be demonstrated both using base cells consisting of continuum elements and base cells consisting of beam elements. The beam element base cell is included with inspiration from experimental results in (Schaedler, 2011), where a highly energy absorbing material, constructed from structural elements with a small cross sectional area but large area moment of inertia, is presented. Furthermore, the applicability of multiscale finite element methods (Efendiev, 2009) to account for boundary conditions of periodic structures that possess a finite extent is investigated.