



Influence of micro- and nanofillers on DEAP performance

Skov, Anne Ladegaard; Bejenariu, Anca Gabriela; Daugaard, Anders Egede

Publication date:
2011

[Link back to DTU Orbit](#)

Citation (APA):

Skov, A. L., Bejenariu, A. G., & Daugaard, A. E. (2011). *Influence of micro- and nanofillers on DEAP performance*. Abstract from 6th World Congress on Biomimetics, Artificial Muscles and Nano-Bio, Cergy-Pontoise, France. <http://biomimetics2011.u-cergy.fr/>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Influence of micro- and nanofillers on DEAP performance

Anne Ladegaard Skov, Anca Bejenariu, Anders Egede Daugaard
DTU - Chemical Engineering
Soeltofts Plads Bygn 229, DK-2800 Kgs Lyngby
al@kt.dtu.dk

Type of presentation: Oral

The formulation of dielectric electroactive polymers (DEAP) is a challenging task as the elastomer part of DEAP is a multi-component system with strict requirements to the electromechanical performance. In traditional formulated products such as paints there is a huge variety of filler materials available and the filler particles are used both to lower the price and to increase the performance of the material. In DEAP there is a strong interplay between the electrical and mechanical properties as one property may be improved and another worsened when changing the formulation so in many cases optimization of the properties ends in a trade-off of some kind.

In this study we focus on the addition of well-known commercially available filler particles and evaluate their performance in elastomers applied for DEAP since the price of the fillers also have to be taken into account when formulating. The effect of particle size and particle size distribution on the electrical and viscoelastic properties is investigated. Both nano- and microscale particles of different compositions are mixed with a platinum cured silicone elastomer matrix [1] in different combinations, and the dielectric and viscoelastic properties are measured.

The dielectric properties are improved mainly by decreasing the particle size as was also shown by Kofod et al [2] for acrylic networks whereas the elastic properties are influenced in a less trivial way. The filler particles increase the storage modulus and make the films easier to handle but the formulation of the 'raw' silicone matrix has to be modified as the filler particles in some instances interact with the polymers and hence require a changed stoichiometry to ensure complete reaction of both reactive species in the silicone matrix.




Figure: Illustrations of different particle size distributions and of an LVE diagram for a typical elastomer with a small degree of viscous dissipation.

References:

- [1] A. L. Larsen, K. Hansen, P. Sommer-Larsen, O. Hassager, A. Bach, S. Ndoni, and M. Jørgensen, *Macromolecules* 2003, 36, 10063.
- [2] Mc Carthy DN, Risse S, Katekomol P, Kofod G J., *Physics D-Appl. Phys.* 2009, 42, 14, 145406.