



Fabrication and performance of high temperature segmented thermoelectric oxide-based module

Le, Thanh Hung; Pham, Hoang Ngan; Han, Li; Holgate, Tim; Van Nong, Ngo; Linderoth, Søren; Pryds, Nini

Publication date:
2013

[Link back to DTU Orbit](#)

Citation (APA):

Le, T. H., Pham, H. N., Han, L., Holgate, T., Van Nong, N., Linderoth, S., & Pryds, N. (2013). *Fabrication and performance of high temperature segmented thermoelectric oxide-based module*. Abstract from 32nd International Conference on Thermoelectrics, Kobe, Japan.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Fabrication and performance of high temperature segmented thermoelectric oxide-based module

LE THANH HUNG, PHAM HOANG NGAN, LI HAN, TIM HOLGATE, NGO VAN NONG,
SOREN LINDEROTH and NINI PRYDS

Technical University of Denmark

In order to improve the power generation performance of oxide modules, segmented p-legs of half-Heusler (HH) alloy $Zr_{0.5}Hf_{0.5}CoSb_{0.8}Sn_{0.2}$ to layered-colbatite $Ca_3Co_4O_9$ and n-legs doped-ZnO were used. The thermoelectric properties of both single and segmented legs were characterized from 300 to 1100 K. Using these data as input parameters, segmented module was first theoretically designed by 1D numerical modeling, in which the compatibility factor of HH alloy and oxides were taken into consideration to maximize the efficiency of their segmentation. Based on the modeling strategy design, segmented modules were constructed, tested, and its performance is compared with theoretical result and with non-segmented oxide modules.