



## Preparation and Characterization of Anisotropic Films by Curing Hard Silicone Microspheres with Soft Silicone

Gonzalez, Lidia; Skov, Anne Ladegaard

*Publication date:*  
2012

[Link back to DTU Orbit](#)

*Citation (APA):*

Gonzalez, L., & Skov, A. L. (2012). *Preparation and Characterization of Anisotropic Films by Curing Hard Silicone Microspheres with Soft Silicone*. Abstract from 49th Nordic Polymer Days 2012, Copenhagen, Denmark. <http://www.npd2012.dk/>

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Preparation and Characterization of Anisotropic Films by Curing Hard Silicone Microspheres with Soft Silicone

*Lidia González and Anne Ladegaard Skov*

*The Danish Polymer Centre, Department of Chemical and Biochemical Engineering,  
Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark  
ligo@kt.dtu.dk*

Poly(dimethylsiloxanes) (PDMS) have unique properties such as elastic behaviour and resistance to high temperatures, light degradation and chemical attack.[1] These exceptional features make cross-linked PDMS suitable for a wide range of applications such as in electrical and/or optical devices [2], anticorrosion [3], sealants and adhesives [4] and biomedical applications [5]. Furthermore an elastomer is a crosslinked polymeric material with the capacity of going back to its original size and shape after being deformed. The aim of this work is to prepare anisotropic silicone materials by curing hard silicone microspheres with soft silicone (**Fig.1**) and studying the effects of hard silicone microspheres on the properties of polysiloxane elastomer. (**Fig.2**)




Figure 1. Soft silicone film with hard silicone microspheres




Figure 2. Behaviour of the film after stretching.

The films were prepared by curing two silicone systems: the hard silicone microspheres, which are prepared by using Sylgard 184, a common PDMS elastomer kit from Dow Corning, and the soft silicone that is based on vinyl terminated PDMS (DMS-V35 with  $M_n=49500$  g/mol). The analysed parameters, which directly influence the properties of the films, are: a) excess of vinyl groups in hard microspheres, b) size distribution of microspheres and c) excess of hydride groups ( $r > 1$ , where  $r$  is defined as the stoichiometric imbalance). Finally, the films were characterized by rheological (dynamic viscoelastic) properties and extensional experiments.

## References

- [1]. Owen M. J. Siloxane polymers, 1st ed. Englewood Cliffs, NJ: Prentice Hall; 1993
- [2]. Morent R, De Geyter N, Axisa F, De Smet N, Gengembre L, De Leersnyder E, et al. Phys D Appl Phys 2007;40:7392–401.
- [3]. Wu KH, Chao CM, Yeh TF, Chang TC. Surf Coat Technol 2006;201:5782–8.
- [4]. Buyl F. Int J Adhes Adhes 2001;21:411–22.
- [5] a) Ikada Y. Biomaterials 1994;15:725–36; b) Abbasi F, Mirzadeh H, Katbab A. Polym Int 2002;51:882–8.