



Lamination of PDMS films by different methods

Hassouneh, Suzan Sager; Yu, Liyun; Skov, Anne Ladegaard

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Hassouneh, S. S., Yu, L., & Skov, A. L. (2012). *Lamination of PDMS films by different methods*. Abstract from 49th Nordic Polymer Days 2012, Copenhagen, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Lamination of PDMS films by different methods

Suzan Hassouneh, LiyunYu and Anne Ladegaard Skov

*The Danish Polymer Centre, Department of Chemical and Biochemical Engineering,
Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark
shas@kt.dtu.dk*

The interest in elastomers has increased over the last decades due to the versatility of the material. Elastomers used for electro active polymers (EAP) have received a lot of interest. Especially PDMS has shown promising features.

The aim of this work is therefore to investigate different methods on how to laminate two PDMS film together since this is a currently a crucial step in the production of EAP films. One investigated method (**method 1**) is to use an amino silane (bis(3-(trimethoxy)propyl)amine) as an adhesive. The other investigated method (**method 2**) is to plasma treat the surface of the films and adhere them together.



Figure 1: Apparatus to determine the peel strength.

The films were prepared by curing the commercially available elastomer Elastosil RT 625 from Gelest. For both methods the process conditions and the peel strength (**figure 1**) are investigated. The investigated process conditions for method 1 are the amount of the amino silane in the interface and the time it needs before it is adhered, and for method 2 the time it takes the films to fully adhere.