



## The photonic nanowire: An emerging platform for a highly efficient quantum light source

Gregersen, Niels; Claudon, J.; Munsch, M.; Bleuse, J.; Delga, A.; Mørk, Jesper; Gerard, J. M.

*Publication date:*  
2014

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*

Gregersen, N., Claudon, J., Munsch, M., Bleuse, J., Delga, A., Mørk, J., & Gerard, J. M. (2014). *The photonic nanowire: An emerging platform for a highly efficient quantum light source*. Abstract from 35th Progress In Electromagnetics Research Symposium , Guangzhou (Canton), China.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# The photonic nanowire: An emerging platform for a highly efficient quantum light source

N. Gregersen<sup>1</sup>, J. Claudon<sup>2</sup>, M. Munsch<sup>2</sup>, J. Bleuse<sup>2</sup>, A. Delga<sup>2</sup>, J. Mørk<sup>1</sup> and J. M. Gérard<sup>2</sup>

<sup>1</sup>DTU Fotonik, Department of Photonics Engineering, Technical University of Denmark, Denmark

<sup>2</sup>CEA-CNRS-UJF Joint Group 'Nanophysique et SemiConducteurs' CEA, INAC, SP2M, France

**Abstract**— The single-photon source capable of emitting single indistinguishable photons on demand represents a key component in quantum information applications. The photonic nanowire represents an attractive platform to construct a source with near-unity efficiency.

## 1. INTRODUCTION

An optically or electrically triggered quantum light emitter, e.g. a semiconductor quantum dot (QD), embedded in a solid-state semiconductor host material appears as an attractive platform for deterministic generation of single photons. However, for a QD in bulk material, the large index contrast at the semiconductor-air interface leads to a collection efficiency of only 1-2 %, and efficient light extraction thus poses a major challenge in single-photon source engineering. [1]

The photonic nanowire is a vertical GaAs cylinder with an embedded InAs QD placed on a substrate with an emission wavelength of  $\approx 950$  nm. By choosing a proper nanowire radius, the spontaneous emission into radiation modes can be strongly suppressed, and the probability for an on-axis QD of emitting photons into the fundamental  $HE_{11}$  mode can be close to unity. The design features no cavity and does not rely on resonant cQED effects, meaning that efficient coupling from the QD to the guided mode is obtained over a broad spectral range. No spectral alignment between the emitter line and a narrow cavity line is required, which represents a huge practical advantage in the fabrication.

To control the light emission and ensure a high collection efficiency, two additional elements must be included. While photons are efficiently funneled into the nanowire fundamental mode, half of the light will propagate towards the substrate due to the nanowire mirror symmetry. It is thus necessary to implement a bottom metal mirror to reflect this light back towards the top. Furthermore, the optimum nanowire diameter is only  $\approx \lambda/4$  leading to a narrow mode waist and a highly divergent far field emission pattern of the truncated nanowire. A conical tapering strategy is thus required allowing for an adiabatic expansion of the fundamental mode and narrow output beam waist.

The original optically pumped photonic nanowire design implements regular conical taper, and its first experimental demonstration featured an efficiency of 0.72. However, for applications, electrical contacting is desired, and a novel photonic trumpet design based on an inverted conical tapering compatible with the implementation of a top metal contact has recently been proposed. The trumpet features a strongly Gaussian far-field emission, and a first implementation of this strategy [2] has very recently lead to an ultra-bright single-photon source with a first-lens external efficiency of 0.75 and a predicted coupling to a Gaussian beam of 0.61.

## ACKNOWLEDGMENT

This work was funded by project SIQUTE (contract EXL02) [3] of the European Metrology Research Programme (EMRP). The EMRP is jointly funded by the EMRP participating countries within EURAMET and the European Union.

## REFERENCES

1. Gregersen, N., Kaer, P., and Mørk, J., "Modeling and Design of High-Efficiency Single-Photon Sources," *IEEE J. Sel. Top. Quantum Electron.*, Vol. 19, 9000516, 2013.
2. Munsch, M., Malik, N. S., Bleuse, J., Dupuy, E., Delga, A., Gérard, J. M., Claudon, J., Gregersen, N., and Mørk, J., "Dielectric GaAs Antenna Ensuring an Efficient Broadband Coupling between an InAs Quantum Dot and a Gaussian Optical Beam," *Phys. Rev. Lett.*, Vol. 110, 177402, 2013. "Erratum," *Phys. Rev. Lett.*, Vol. 111, 239902, 2013.
3. <http://www.ptb.de/emrp/siqute-home.html>